The floorstanding 950F, compact LCR950 front and SUR95T Tripole surround speaker all share the innovative high frequency driver developed for the latest versions of our legendary professional studio monitors. Expressly built for high power handling with minimal dynamic compression, the 950 tweeter delivers full dynamic range at high output levels with an openness and airiness far beyond loudspeakers of comparable size and cost.

All MK Sound 950 loudspeakers are designed from the ground up as an integral system for extreme realism and three-dimensional holographic imaging in collaboration with any MK Sound subwoofer. To achieve these objectives, all models employ exclusive, identical 5.25" polypropylene woofers, integrated with the groundbreaking MK Sound Pro tweeter via the exclusive MK Sound Phase Focused crossover.

With deceptively modest dimensions, an MK Sound 950 stereo or surround system offers superb sound quality with a minimal footprint in any living space.

The heavy, curved metal grilles are acoustically inert and are held in place with magnets concealed in the front baffle. This design eliminates the annoying buzz or rattle that typically occurs when other brands dress up their products with cheap, lightweight plug-in metal or plastic fronts. The MK Sound 950 offers contemporary visual appeal at no sacrifice in audio performance.

Critical home entertainment enthusiasts and serious audio professionals find rare common ground in acknowledging

MK Sound as the pinnacle of loudspeaker performance for music mixing, mastering, broadcast and film sound production or simply for kicking back and relaxing at home with your favorite music and movies.

MK Sound 950 loudspeakers are designed for use with a high performance subwoofer. For guidance in subwoofer selection, contact your local authorized MK Sound dealer.

The 950 system proudly lives up to the MK Sound tradition as The Choice of Professionals and Perfectionists.



The original THX program was created to ensure that movie theaters meet strict quality standards. The THX logo

immediately became recognized as a seal of approval for quality-conscious cinema-goers around the world.

For the home theater enthusiast, the independent THX Select2 quality standard ensures high performance in listening environments up to 2,000 cubic feet.

The 950 THX Select2 Series meets and exceeds THX Select2 specifications for flat on-axis frequency response, wide and even horizontal dispersion and coverage of a large listening area with consistent tonal character.

For further information, contact your local authorized MK Sound dealer or visit MK Sound at www.mksoundsystem.com.





- All-New Professional High Frequency Driver
- Exclusive Phase-Focused Crossovers with
  Time Domain Analysis, Frequency Domain Analysis
  and Points-In-Space Analysis
- Voice-Matched Satellites and Surrounds
- Compact or Floorstanding Configuration
- Ideal Tripole Surround Dispersion
- Stylish Finish with Metal Mesh Grilles

MKSOUND

www.mksoundsystem.com

MKMKSOUM

www.gramco.ak - 10:2011

## 950F Monitor

By popular demand, MK Sound now offers our first-ever floorstanding monitor, the 950F, in a slim-line enclosure, 120 cm (47.2") in height. While particularly attractive as a noholds barred music solution, MK Sound 950F is also up to the task of rendering demanding modern movie soundtracks with abundant verve and vitality.

In partnership with any MK Sound subwoofer, the sealed 950F enclosure ensures ideal integration across the full musical spectrum. At virtually any listening position, the audience will experience superior three-dimensional imaging and clarity for remarkable sonic realism.

The MK Sound 950F system draws heavily on technologies and components created for its famed professional and domestic siblings, while sporting its own distinctive metal mesh grilles for an attractive, upscale designer feel that blends well with contemporary and traditional environments.

The innovative MK Sound Pro tweeter employs a coated silk dome with lightweight copper-clad aluminum wire and mounted in a calibrated waveguide for controlled directivity and integration with the bass/mid array. To match its fresh level of high frequency resolution, the MK Sound 950F bass/mid driver maintains the legendary top-to-bottom integrity and cohesion that is the hallmark of MK Sound.

The impressive, effortless power handling of the 950F confirms that the speaker's contemporary visual appeal comes at no sacrifice in audio performance.



## LCR950 Monitor Satelite

The exceptional performance of the MK Sound 950 range is in large part due to unlimited access to technologies and parts developed in the pursuit of audio nirvana for the critical professional user by our professional division.

Crucial to the consistency and seamless soundfield generated by any 950 system, front and rear speakers employ the same innovative drivers, crossover components and technologies. While this may seem like common sense, many so-called music and surround "systems" are in fact a hodgepodge of random odds and ends.

The arrival of the MK Sound 950 compact loudspeaker has been celebrated with high praise from all quarters. Expectations naturally ran high for a system of such distinguished pedigree, slotted to fit in the MK Sound range between the acclaimed 750 THX Select2 system and the legendary 150 THX Ultra2 system.

Unlike other crossover designs that are optimized only for a narrow and shallow "sweet spot", proprietary MK Sound Phase Focused crossovers deliver razor-sharp imaging and flat frequency response over a very wide listening area by optimizing system performance in both the vertical and horizontal planes.

Three identical front speakers ensure a coherent, consistent image, while handling micro-details and subtle nuances with a delicate touch. Extraordinary dynamics lend substance and weight for a realistic sense of power.

## SUR95T Tripole Surround

The SUR95T Tripole surround loudspeaker allows multichannel home entertainment enthusiasts to enjoy MK Sound Tripole® technology in a practical size for side or rear placement in a 5.1, 6.1 or 7.1 channel configuration that won't dominate your living space.

The SUR95T Tripole delivers both imaging specificity and an enveloping soundfield, because it is essentially two independent speakers (a front-radiating monopole and a side-radiating dipole) mounted in a single cabinet. This breakthrough design shares all of the technologies and is timbre matched to the LCR950 and the 950F.

Featuring two 3" pulp mid-tweeters on each side of the cabinet oriented in dipole fashion, the dipole configuration emits diffuse sound throughout the room. Combined with the front-mounted 1" silk dome tweeter and 5.25" polypropylene mid-woofer direct radiating configuration, the Tripole design provides even distribution of sound throughout the listening area with pinpoint accuracy

> The SUR95T Tripole surround is the ideal match for the LCR950 and the 950F in output, timbre and overall sound quality.



Coated silk dome with

lightweight, copper-clad

and high sensitivity

aluminum wiring for low mass

· Semi-shielded magnet system based on large ferrite double magnet to optimize distribution of magnetic flux in the air gap




MISOUNI

Unique low-compression rea chamber tubes for minimal distortion and controlled transient response, especially

at the bottom end of the

 Elimination of build-up of captive air mass behind the dome thanks to double flow resistor foam plug in vented pole piece for enhanced speed and precision across the high frequency range

Vents in high sensitivity ferrofluid cooled voice coil for reduced compression at large excursions



950F Specifications

. . . . . Black Satin with black metal mesh grille Drivers . . . . . . 1" silk dome ferrofluid double ferrite magnet tweeter 2 x 5.25" polypropylene bass/mid Frequency Response . . . . . . . . . 80 Hz - 20 kHz ±3 dB Dimensions (HxWxD) . . . . . . . 47.2 x 7 x 8.3" - 120 x 17.8 x 21.0 cm 

and an enveloping soundfield.

LCR950 Specifications

. Black Satin with black metal mesh grille Drivers . . . . . 1" silk dome ferrofluid double ferrite magnet tweeter 2 x 5.25" polypropylene bass/mid Frequency Response . . . . . . . . . 80 Hz - 20 kHz ±3 dB Dimensions (HxWxD) . . . . . . . 16.1 x 7 x 9" – 40.8 x 17.8 x 22.8 cm **SUR95T Specifications** 

Finish . . . . . . . . . Black Satin with black metal mesh grille Drivers . . . . . 1" silk dome ferrofluid double ferrite magnet tweeter 5.25" polypropylene bass/mid 2 x 3" coated paper (side-mounted) Dimensions (HxWxD) . . . . . . . . 10.2 x 7 x 8.7" – 25.9 x 17.8 x 22.1 cm